

Corporate Hazard Identification & Risk Control

HIRA # 15.25

Formwork and Falsework

Applicable Zones:	Project Yard Office Asphalt Plant				
HAZARD(S)					
 Struck By (P) Dropped Objects (P) Fall from Height (P) Poor Housekeeping (P) 					
Improper Equipment (P)					

PRE-CONTROL RISK					
Likelihood	Consequence	Pre-Control Risk			
4	5	20			

CONTROLS				
Elimination	Using hand signals and radios to communicate with crane operators can remove workers from hazardous situations.			
Substitution	If there is any other equipment that can be used to complete the task, it should be, even extension of tool handles or similar design changes.			
Engineering	Travel restraint must be used first over fall arrest, if able.			
Administrative	A site specific fall arrest plan must be in place and trained on.			
PPE	High Visibility Clothing, Hard Hat & Safety Boots at a minimum must be worn at all times.			

POST CONTROL RISK					
Likelihood	Consequence	Post-Control Risk	Risk Reduction	Critical or Not Critical	
2	5	10	10	Yes	

LEGISLATIVE REFERENCES	OTHER STANDARDS & REFERENCES		
	J-AAR Manual: P2.11.6		
O.Reg 213/91: Part 2 S.87-92	J-AAR Manual: P2.11.11		
O.Reg 213/91: Part 2 S.125-156	J-AAR Manual: P2.12.11.6		
O.Reg 213/91: Part 2 S. 157-180	J-AAR Manual: P2.12.11.7		
	J-AAR Manual: P2.12.11.11		