

Corporate Hazard Identification & Risk Control

HIRA # 15.41

Ladders

Applicable Zones:	Project Yard	Office	Asphalt Plant		
HAZARD(S)					
Slip, Trip and Fall (P)					
 Musculoskeletal Disorders (P) 					
 Equipment Failure (P) 					

	PRE-CONTROL RISK				
Likelihood 3	Consequence 5	Pre-Control Risk 15			
CONTROLS					

CONTROLS

Elimination | Is a ladder required? If the work can be completed with equipment or a specialized tool, please do so.

Substitution | If the area is not acceptable for ladder use, then please use scaffolding or some other elevated platform.

Engineering | Tie off ladder at top and bottom, make sure it is placed on firm level ground.

Administrative | Ladder inspection must be completed prior to each use.

High Visibility Clothing, Hard Hat & Safety Boots at a minimum must be worn at all times. Needs to be inspected before each use.

POST CONTROL RISK					
Likelihood	Consequence	Post-Control Risk	Risk Reduction	Critical or Not Critical	
2	5	10	5	Yes	

LEGISLATIVE REFERENCES	OTHER STANDARDS & REFERENCES	
O.Reg 213/91: S. 78-86	J-AAR Manual: P1.4.11	
O.Reg 854: S. 46-54	J-AAR Manual: P1.5.4.11	