

## Corporate Hazard Identification & Risk Control

HIRA # 15.58

## **Power Elevated Work Platform**

Applicable Zones: Project	Yard	Office	Asphalt Plant		
<ul> <li>HAZARD(S)</li> <li>Working at Heights (P)</li> <li>Multi-vehicle collision (P)</li> <li>Rollover (P)</li> <li>Machine Hazards (P)</li> </ul>					
Pinch Points (P)  PRE-CONTROL RISK					
Likelihood	Consequenc	е	Pre-Control Risk		

CONTROLS				
Elimination	Do not use an elevated work platform where scaffolding can be erected.			
Substitution				
Engineering	gineering A signal person shall be designated whenever backing up is required.			
Administrative	If they are required on site a training program must be completed by the operator prior to			
	the use.			
PPE	High Visibility Clothing, Hard Hat & Safety Boots at a minimum must be worn at all times.			

POST CONTROL RISK					
Likelihood	Consequence	Post-Control Risk	Risk Reduction	Critical or Not Critical	
2	5	10	5	No	

LEGISLATIVE REFERENCES	OTHER STANDARDS & REFERENCES
O.Reg 213/91: S. 125 O.Reg 213/91: S.143-149	J-AAR Manual: P2.11.11 J-AAR Manual: P2.12.11.11 J-AAR Manual: P2.12.11.12