



# Corporate Hazard Identification & Risk Control

HIRA #  
15.63

## Spill Clean-Up

<b>Applicable Zones:</b>	Project		Yard		Office		Asphalt Plant	
--------------------------	---------	--	------	--	--------	--	---------------	--

### HAZARD(S)

- Exposure to Chemicals (P)
- Environmental Damage (P)
- Occupational Illness (H)
- Eye/Skin Irritation (H)
- Risk of Fire (P)

### PRE-CONTROL RISK

Likelihood 2	Consequence 5	<b>Pre-Control Risk 10</b>
-----------------	------------------	--------------------------------

### CONTROLS

<b>Elimination</b>	Inspection of tanks and the use of double walled containers should be used whenever possible.
<b>Substitution</b>	If environmentally friendly and safe products can be used, they need to be.
<b>Engineering</b>	Spill Kit Locations must be included in the workers' orientation on their first day on site.
<b>Administrative</b>	SDS's must be consulted before chemical use for safe clean up procedures.
<b>PPE</b>	High Visibility Clothing, Hard Hat & Safety Boots at a minimum must be always worn.

### POST CONTROL RISK

Likelihood 1	Consequence 5	<b>Post-Control Risk 5</b>	Risk Reduction 5	Critical or Not Critical No
-----------------	------------------	--------------------------------	---------------------	-----------------------------------

### LEGISLATIVE REFERENCES

O.Reg 213/91: S. 37-38  
O.Reg 213/91: S. 256  
WHMIS 2015 Regulations

### OTHER STANDARDS & REFERENCES

J-AAR Manual – P1.4.1  
J-AAR Manual – P1.5.4.1  
J-AAR Manual – P1.3.14